

VFC HOIST SC200GD (0~36m/min)

Characteristic:

- ✧ Power saving, Start current much lower.
- ✧ Frequency control, Run smoothly at starting and braking.
- ✧ Small structural impact, low mechanical wear.
- ✧ Use 3*11kw Chinese motor and SIEMENS inverter.

Technical Data:

Name	Unit	Parameter
Payload capacity	Kg	2000
Speed	m/min	0~36
Max. lifting height	m	600
Erection load capacity	kg	1000
Lifting device capacity	Kg	250
Safety device		SAJ40
Motor control		VFC
Power supply		380V/50Hz/3Phase
Motor power	KW	3×11, Chinese motor
Motor rated current	A	69
Power supply fuses	A	80
Power supply capacity	KVA	≥46
Freq. converter power	KW	37 (WEICHI)
Cage size	m	3.2×1.5×2.35
Door opening	m	1.42×2.0
Mast section type	m	0.65×0.65×1.508



We adhere to the principle of safety and quality first, to provide customers with safe and reliable products.

徐州延兴工程机械有限公司 xuzhou yanxing construction machinery Co.,Ltd

地址：徐州延兴工程机械有限公司
ADD:Room 1419-1420 Block B city plaza yunlong district
xuzhou city Jiangsu province China

TEL: +86-83605558

FAX: +86-83663060

www.yasmin.cc
Post code :221000

VFC HOIST SC200GD (0~36m/min)

The main part and weight:



Name	Unit	Weight	NOTE
Cage	Kg	1480	The standard cage dimension is $3.2 \times 1.5 \times 2.35\text{m}$, Other available cage dimension (L $\times$ W $\times$ H, m): $2.5 \times 1.3 \times 2.35$, $3.0 \times 1.3 \times 2.35$, $3.2 \times 1.5 \times 2.5$, $3.6 \times 1.5 \times 2.5$, $3.8 \times 1.5 \times 2.5$, $4.0 \times 1.5 \times 2.5$, $4.2 \times 1.5 \times 2.5$. If in doubt, please contact the technical department of
Driving machine	Kg	700	
Enclosure	Kg	1300	
Mast section (Double racks)	Kg	125 ($\phi 76 \times 4.5$)	
		145 ($\phi 76 \times 6$)	
		165 ($\phi 76 \times 8$)	
		185 ($\phi 76 \times 10$)	

徐州延兴工程机械有限公司 xuzhou yanxing construction machinery Co.,Ltd

地址：徐州延兴工程机械有限公司
ADD:Room 1419-1420 Block B city plaza yunlong district
xuzhou city Jiangsu province China

TEL: +86-83605558

FAX: +86-83663060

www.yasmin.cc
Post code :221000